



BEAMER INSERT

The Beamer Insert is a recessed down-light for outdoor as well as for indoor applications. The Beamer Insert is equipped with the latest high power leds in mono-chrome or RGB.

This fitting exists in two versions: Beamer 1 Insert, equipped with a 1 W Poweredled and the Beamer 3 Insert equipped with a 3 W Poweredled or a 3W RGB Poweredled.

In order to produce an optimum cooling for the led, the housing is made out of anodized aluminium.

A wide selection of light colours are available as well as a possibility between narrow beam (10°) and medium beam (30°). The led is fixed by means of stainless steel screws. This ensures an easy replacement in case of failure. The Beamer Insert is installed by means of stainless steel springs.

Power: 1 W - 3 W

remote powersupply type: current




TECHNICAL SPECIFICATIONS BEAMER INSERT

Poweredled	Colours	Optics	mA	IP	housing	cable	fixation	cut out	current drive	power supply
1 x 1W	R-G-B-A CW-WW	10° 30°	350	IP 65	alu ano	0,5 m	springs	37 mm	6/12 led 350 mA	110-230 V AC
1 x 3W	R-G-B-A CW-WW	10° 30°	700	IP 65	alu ano	0,5 m	springs	37 mm	6/12 led 700 mA	110-230 V AC
1 x 3W	RGB	30°	350	IP 65	alu ano	0,5 m	springs	37 mm	RGB drive 350 mA	12-48 V DC

ARTICLE NUMBERS BEAMER INSERT / N° 3141...12

	R	G	B	A	WW	CW	RGB
1W/10°	112	113	115	116	110	111	
1W/30°	312	313	315	316	310	311	
3W/10°	512	513	515	516	510	511	
3W/30°	712	713	715	716	710	711	721



LED INSTRUMENTS

ALLAEYS LED INSTRUMENTS
 Wortegemseweg 121 - B-8790 WAREGEM - BELGIUM
 phone: +32 56 616 274 - fax: +32 56 616 275
 mobile phone +32 495 564 072
 e-mail: main@allaey's.com