

# BEAMER SURFACE

The Beamer Surface is a surface mounted projector for outdoor as well as indoor applications. The Beamer Surface is equipped with the latest high power leds in monochrome or RGB.

This fitting exists in two versions:

The Beamer 1 Surface, equipped with a 1W monochrome powered and the Beamer 3 Surface equipped with a 3W monochrome powered or a 3W RGB power led.

In order to produce an optimum cooling for the led, the housing is made out of anodized aluminium.

A wide selection of light colours is available as well as a possibility of narrow beam (10°) or wide beam (30°)

The led is fixed by means of stainless steel screws. This ensures an easy replacement in case of failure. The projector is fixed by means of a high grade stainless steel mountain bracket.

Power: 1 W - 3 W

remote powersupply type: current




## TECHNICAL SPECIFICATIONS BEAMER SURFACE

Powered	Colours	Optics	mA	IP	housing	cable	fixation		current drive	power supply
1 x 1W	R-G-B-A CW-WW	10° 30°	350	IP 65	alu ano	0,5 m	bracket		6/12 led 350 mA	110-230 V AC
1 x 3W	R-G-B-A CW-WW	10° 30°	700	IP 65	alu ano	0,5 m	bracket		6/12 led 700 mA	110-230 V AC
1 x 3W	RGB	30°	350	IP 65	alu ano	0,5 m	bracket		RGB drive 350 mA	12-48 V DC

## ARTICLE NUMBERS BEAMER SURFACE / N° 2143...12

	R	G	B	A	WW	CW	RGB
1W/10°	112	113	115	116	110	111	
1W/30°	312	313	315	316	310	311	
3W/10°	512	513	515	516	510	511	
3W/30°	712	713	715	716	710	711	721



LED INSTRUMENTS

ALLAEYS LED INSTRUMENTS  
 Wortegemseweg 121 - B-8790 WAREGEM - BELGIUM  
 phone: +32 56 616 274 - fax: +32 56 616 275  
 mobile phone +32 495 564 072  
 e-mail: main@allaeys.com