



# BEAMER TRI SURFACE

The Beamer Tri Surface is a surface mounted spotlight for outdoor as well as for indoor applications. The Beamer Tri Surface is equipped with the latest high power leds in monochrome or RGB. This fitting exists in two versions: Beamer Tri 1 Surface, equipped with three 1 W Powerleds and the Beamer Tri 3 Surface equipped with three 3 W Powerleds or three 3W RGB Powerleds. In order to produce an optimum cooling for the led, the housing is made out of anodized aluminium.

A wide selection of light colours are available as well as a possibility between narrow beam (10°) and medium beam (30°). The leds are mounted on a Metal Core Printed Circuit Board which is fixed by means of stainless steel screws. This ensures an easy replacement in case of failure.

The Beamer Tri Surface is installed by means of a stainless steel bracket.

**Power: 1 W - 3 W**

**remote powersupply type: current**




## TECHNICAL SPECIFICATIONS BEAMER TRI SURFACE

Powered	Colours	Optics	mA	IP	housing	cable	fixation		current drive	power supply
3 x 1W	R-G-B-A CW-WW	10° 30°	350	IP 67	alu ano	1 m	bracket		6/12 led 350 mA	110-230 V AC
3 x 3W	R-G-B-A CW-WW	10° 30°	700	IP 67	alu ano	1 m	bracket		6/12 led 700 mA	110-230 V AC
3 x 3W	RGB	30°	350	IP 67	alu ano	1 m	bracket		RGB drive 350 mA	12-48 V DC

## ARTICLE NUMBERS BEAMER TRI SURFACE / N° 2563...12

	R	G	B	A	WW	CW	RGB
1W/10°	112	113	115	116	110	111	
1W/30°	312	313	315	316	310	311	
3W/10°	512	513	515	516	510	511	
3W/30°	712	713	715	716	710	711	721



LED INSTRUMENTS

ALLAEYS LED INSTRUMENTS  
 Wortegemseweg 121 - B-8790 WAREGEM - BELGIUM  
 phone: +32 56 616 274 - fax: +32 56 616 275  
 mobile phone +32 495 564 072  
 e-mail: main@allaey's.com